AGRICULTURAL AIR ASSISTED TRAILED SPRAYER

MODEL: KX600V600 FX-DOUBLE FAN

SPECIFICATIONS

TANK CAPACITY	:	600 LTR
SUCTION CAPACITY	:	70 LPM / MAX 50 BAR
PUMP TYPE	:	DIAPHRAGM PUMP- MADE IN ITALY
GEAR BOX	:	2 SPEED
FAN	:	SIZE - 600MM (MADE BY DRAGONE-ITALY) FRONT INTAKE STAINLESS STEEL
SPRAY TIPS	:	BLANK CORE / HOLLOW CONE ALBUZ ATR CERAMIC NOZZLES
NOZZLE HOLDER	:	BRAGLIA - M82/65 ADJUSTABLE NOZLES
NO OF NOZZLES	:	10
FILTERS & ,MIXER	:	INCLUSIVE OF SUCTION FILTER 160 LPM & TANK MIXERS
CHASSIS	:	HOT GALVANIZED
SPECIAL FEATURES	:	PTO DRIVEN @540 RPM, WIDE ANGLE SHAFT, SUITABLE TO ALL TRACTORS ABOVE 24 HP
PIPES	:	HIGH PRESSURE HYDRAULIC PIPES
ACCESSORIES	:	SS.NUT, BOLTS AND CLAMPS
CONTROLLER	:	M-170-BRAGLIA-ITALY
WEIGHT	:	401 kg
DIMENSION	:	LWH : 2450x1160x1200)mm

SPECIFICATIONS OF FAN

Blade Angle			Air Speed m/s	Air Volume m^3/hour	Absorbed Power kw
Fan Inclination					
20°			18.2	14300	5.6
35°			25.1	19200	10.3
45°			32.3	24300	14.2
20°			24.2	18300	10.0
35°			33.9	25700	16.2
45°			41.4	32100	19.9